

PP2712 / 2022 / ISSUE 2

# DATASHEET

## SOTERIA UL

### DUAL SWITCH MONITOR MODULE



## PRODUCT OVERVIEW

Product	Dual Switch Monitor Module
Part No.	SA4705-720APO
Digital Communication	XP95 and Discovery

## PRODUCT INFORMATION

The Dual Input Monitor Module is a loop-powered device incorporating a dual monitored input circuit for connection to remote switches, for indoor use only.

- Built-in isolator
- Visible LEDs
- Loop Powered
- Ground fault detection
- Selectable priority to monitor equipment where a fast response is required
- Interrupt facility
- Improved design for ease of wiring

## APPROVALS



### Apollo America Inc.

25 Corporate Drive, Auburn Hills, MI 48326  
Tel: (248)332-3900. Fax: (248)332-8807

Email: [sales.usa@apollo-fire.com](mailto:sales.usa@apollo-fire.com)  
www.apollo-fire.com

## TECHNICAL DATA

All data is supplied subject to change without notice. Specifications are typical at 24 V, 73°F and 50% RH unless otherwise stated.

General	
Product Operating Temperature	32°F to 120°F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL, ULC, FM, CSFM
Dimensions	4.9" W x 4.9" H x 1.175" D
Materials	Housing: UL94 V-0 polycarbonate
Wire Size	12 - 24 AWG

LED Status		
LED Color	Description	XP95/Discovery Compatibility
Green	Polling	x
Yellow (solid)	Isolation	x
Red	Alarm	x

Single Line Circuit (SLC) - Supervised Power Limited	
Supply Voltage	17 V to 28 V DC
Modulation Voltage	5 V - 9 V peak to peak
Supervisory Current	500 $\mu$ A
Switch-on Surge Current	900 $\mu$ A
Alarm/Operated Current, LED ON	1.6 mA per LED
Maximum Loop Current	1 A

Initiating Device Circuit (IDC)	
Wiring Styles	Supervised power limited Class A and Class B
Voltage	3.3 V DC
Line Impedance	100 $\Omega$ Max
End-of-Line Resistors*	47 k $\Omega$

\*Note: A UL listed end-of-line resistor is available at Apollo - Part No. 44251-146



A Halma company

© 2022 Apollo Fire Detectors Ltd.

All information in this document is given in good faith but Apollo Fire Detectors Ltd cannot be held responsible for any omissions or errors. The company reserves the right to change the specifications of products at any time and without prior notice.