

Single Gang Jack Plate for EVC401/PH

Part No. **EVC301/JP**



Overview

- A single gang jack plate designed for use in conjunction with an EVC401/PH portable fire telephone handset on compatible SigTEL emergency voice communication systems.
- Can be mounted on 25mm UK flush or surface single gang back box.
- When the handset (not supplied) is plugged into the Jack Plate it will call the SigTEL master controller from where a two-way speech channel can be opened and instructions communicated.
- Multiple jack plates can be connected to a single SigTEL Master Controller line in stairwells, etc.
- Designed for use in regions where roaming handsets are accepted (typically the Far and Middle East). UK standard BS5839-9 DOES NOT allow the use of these devices.
- Facilitates reliable two-way communication in an emergency between a permanently manned control room and key points of a site.



Technical Specifications

| | |
|--------------------------|---|
| Approvals/certifications | Designed for use in regions where roaming handsets are accepted (typically the Far and Middle East). UK standard BS5839-9 DOES NOT allow the use of these devices |
| Supply/operating voltage | 11V DC derived from a compatible SigTEL Master Controller (drops to 6 V DC when in use). |
| Quiescent current | 1mA. |
| Activation current | 25mA (current draw when handset is in use). |
| Indicators | When the operator in the control room calls the outstation, a pulsed ringing tone sounds at the outstation. |
| Connections | 6.35mm jack socket. |
| Product dimensions (mm) | 85 W x 85 H x 30 D mm (Can be mounted on a standard UK 25mm single gang flush or surface back box). |



Construction & finish Plastic.
IP Rating IP20.
Weight 58g
Operating conditions/temperature -5°C to +40°C. Max relative humidity: 95%.

